

## LNPTM STAT-KONTM COMPOUND DEL32P

## **DESCRIPTION**

LNP STAT-KON DEL32P compound is based on Polycarbonate (PC) resin containing 10% carbon fiber, 15% PTFE. Added features of this grade include: Internally Lubricated, Electrically Conductive, Wear Resistant, Exceptional Processing.

GENERAL INFORMATION	
Features	Electrically Conductive, High Flow, Wear resistant, Carbon fiber filled, High stiffness/Strength
Fillers	Carbon Fiber, PTFE
Polymer Types	Polycarbonate (PC)
Processing Techniques	Injection Molding

INDUSTRY	SUB INDUSTRY	
Electrical and Electronics	Electronic Components	
Industrial	Material Handling	

## **TYPICAL PROPERTY VALUES**

Revision 20231109

PROPERTIES	TYPICAL VALUES	UNITS	TEST METHODS
IMPACT (1)			
Izod Impact, notched, 23°C	90	J/m	ASTM D256
PHYSICAL (1)			
Density	1.32	g/cm³	ASTM D792
Melt Volume Rate, MVR at 300°C/3.8 kg	19	cm³/10 min	ISO 1133
ELECTRICAL (1)			
Surface Resistivity (2)	1.E+02 – 1.E+06	Ω	ASTM D257
INJECTION MOLDING (3)			
Drying Temperature	120	°C	
Drying Time	4	Hrs	
Maximum Moisture Content	0.02	%	
Melt Temperature	305 – 325	°C	
Front - Zone 3 Temperature	320 – 330	°C	
Middle - Zone 2 Temperature	310 – 320	°C	
Rear - Zone 1 Temperature	295 – 305	°C	
Mold Temperature	80 – 110	°C	
Back Pressure	0.2 – 0.3	MPa	
Screw Speed	30 – 60	rpm	

<sup>(1)</sup> The information stated on Technical Datasheets should be used as indicative only for material selection purposes and not be utilized as specification or used for part or tool design.

<sup>(2)</sup> Measurement meets requirements as specified in ASTM D4496.

<sup>(3)</sup> Injection Molding parameters are only mentioned as general guidelines. These may not apply or may need adjustment in specific situations such as low shot sizes, large part molding, thin wall molding and gas-assist molding.



## **DISCLAIMER**

Any sale by SABIC, its subsidiaries and affiliates (each a "seller"), is made exclusively under seller's standard conditions of sale (available upon request) unless agreed otherwise in writing and signed on behalf of the seller. While the information contained herein is given in good faith, SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND NONINFRINGEMENT OF INTELLECTUAL PROPERTY, NOR ASSUMES ANY LIABILITY, DIRECT OR INDIRECT, WITH RESPECT TO THE PERFORMANCE, SUITABILITY OR FITNESS FOR INTENDED USE OR PURPOSE OF THESE PRODUCTS IN ANY APPLICATION. Each customer must determine the suitability of seller materials for the customer's particular use through appropriate testing and analysis. No statement by seller concerning a possible use of any product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right.