

LNPTM LUBRICOMPTM COMPOUND DFL12

DFL-4012 REGION ASIA

DESCRIPTION

LNP LUBRICOMP DFL12 compound is based on Polycarbonate (PC) resin containing 10% glass fiber and 5% PTFE. Added features of this grade include: Wear Resistant.

.

GENERAL INFORMATION		
Features	Wear resistant	
Fillers	Glass Fiber, PTFE	
Polymer Types	Polycarbonate (PC)	
Processing Techniques	Injection Molding	

INDUSTRY	SUB INDUSTRY
Building and Construction	Building Component
Consumer	Sport/Leisure, Personal Accessory, Home Appliances, Commercial Appliance
Electrical and Electronics	Mobile Phone - Computer - Tablets
Industrial	Electrical

TYPICAL PROPERTY VALUES

Revision 20231109

PROPERTIES	TYPICAL VALUES	UNITS	TEST METHODS
MECHANICAL (1)			
Tensile Stress, break	77	MPa	ASTM D638
Tensile Strain, break	3.5	%	ASTM D638
Tensile Modulus, 50 mm/min	4260	MPa	ASTM D638
Flexural Stress	124	MPa	ASTM D790
Flexural Modulus	4230	MPa	ASTM D790
IMPACT (1)			
Izod Impact, unnotched, 23°C	740	J/m	ASTM D4812
Izod Impact, notched, 23°C	120	J/m	ASTM D256
THERMAL (1)			
HDT, 1.82 MPa, 3.2mm, unannealed	139	°C	ASTM D648
PHYSICAL (1)			
Density	1.3	g/cm³	ASTM D792
FLAME CHARACTERISTICS (2)			
UL Yellow Card Link	E207780-101344587	-	-
UL Recognized, 94V-1 Flame Class Rating	≥3	mm	UL 94



- (1) The information stated on Technical Datasheets should be used as indicative only for material selection purposes and not be utilized as specification or used for part or tool design.
- (2) UL Ratings shown on the technical datasheet might not cover the full range of thicknesses and colors. For details, please see the UL Yellow Card.

DISCLAIMER

Any sale by SABIC, its subsidiaries and affiliates (each a "seller"), is made exclusively under seller's standard conditions of sale (available upon request) unless agreed otherwise in writing and signed on behalf of the seller. While the information contained herein is given in good faith, SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND NONINFRINGEMENT OF INTELLECTUAL PROPERTY, NOR ASSUMES ANY LIABILITY, DIRECT OR INDIRECT, WITH RESPECT TO THE PERFORMANCE, SUITABILITY OR FITNESS FOR INTENDED USE OR PURPOSE OF THESE PRODUCTS IN ANY APPLICATION. Each customer must determine the suitability of seller materials for the customer's particular use through appropriate testing and analysis. No statement by seller concerning a possible use of any product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right.