

# PLUG-IN WITH SABIC'S SPECIALTY MATERIALS WELL-SUITED FOR FAST CHARGING ELECTRIC VEHICLE SERVICE EQUIPMENT

## The electric vehicle (EV) charging infrastructure is growing rapidly throughout the world.

Charging needs and locations for EV's will be supported through several mediums: charging at home, at work, or on the road. Regardless of where you are charging, SABIC's LNP<sup>TM</sup> THERMOCOMP<sup>TM</sup> compound and LNP<sup>TM</sup> ELCRIN<sup>TM</sup> iQ resins can provide superior impact & chemical resistance, high surface aesthetics, high weatherability and superior UV resistance, to name a few. This material would be well-positioned in applications such as sockets, cabinet housings, and charger cables.

### EV CHARGER CABINET HOUSING & CHARGER HANDLE HOUSING

#### **KEY FEATURES:**

- Design freedom
- High aesthetics
- Excellent weatherability & UV stability
- Flame performance V0 at 0.75mm to 3mm, 5VA at 2mm to 4mm, non-Br, non-Cl
- Toughness & high impact

- Chemical resistance
- Light weighting potential up to 15%
- Sustainable solutions available





#### **EV CHARGING SOCKET**

#### **KEY FEATURES:**

- CTI PLC 0 performance
- High RTI >130°C
- Good processability
- High stiffness
- Flame performance Non BR non CL
- Good chemical resistance
- Sustainability solutions available

#### SABIC EVSE SOLUTIONS

|                            |                                | LNP™ ELCRIN™<br>WF0061iQ resin<br>SOCKET                           | LNPTM THERMOCOMPTM DX09402 compound HOUSING                                   | LNPTM ELCRINTM<br>610009UXiQ resin<br>HOUSING      |
|----------------------------|--------------------------------|--|---|--|
|                            |                                |  |   |  |
| PART<br>PERFORMANCE        | Vandalism proof,<br>ductility  | High stiffness   | Good impact,<br>Design for structural<br>foam (up to 15% weight<br>reduction) | Good impact,<br>Ductile at -30°C                   |
| SAFETY,<br>RELIABILITY     | Flame<br>performance           | V0 at 0.8 mm 5VA at 1.5<br>mmGWFI 960°C at 0.8<br>mmNon-Br, non-Cl | V0 at 3mm (foam part)<br>5VA at 4mm (foam part)<br>Non-Br, Non-Cl             | V0 at 0.63mm<br>5VA at 2.5mm<br>GWFI 960°C at 1 mm |
|                            | Electrical performance         | RTI 140°CCTI PLC 0   | _   | RTI 120°C<br>CTI PLC 2                             |
|                            | Thermal performance            | Ball pressure test 175°C   | _   | Ball pressure test 125°C                           |
|                            | Environmental                  | f1   | F1  | f1   |
|                            | Sustainability                 | 25% PCR content  | _   | 19% PCR content                                    |
| AESTHETICS                 | UV resistance<br>Color-ability | Excellent  | Excellent   | Excellent  |
| RESISTANCE<br>TO CHEMICALS |                                | Excellent  | Good  | Excellent  |

#### CONTACT INFORMATION

#### **AMERICAS**

SABIC Americas E productinquiries@sabic.com T +1-800-845-0600

#### **ASIA PACIFIC**

SABIC Shanghai E asiaproductinquiries@sabic.com T +86 400 833 1033

#### **EUROPE**

SABIC Bergen op Zoom E webinquiries@sabic.com T +31 164 292 911







MATERIAL FINDER

LINKEDIN

DISCLAIMER: THE MATERIALS, PRODUCTS AND SERVICES OF SAUDI BASIC INDUSTRIES CORPORATION (SABIC) OR ITS SUBSIDIARIES OR AFFILIATES ("SELLER") ARE SOLD SUBJECT TO SELLER'S STANDARD CONDITIONS OF SALE, WHICH ARE AVAILABLE UPON REQUEST. INFORMATION AND RECOMMENDATIONS CONTAINED IN THIS DOCUMENT ARE GIVEN IN GOOD FAITH. HOWEVER, SELLER MAKES NO EXPRESS OR IMPLIED REPRESENTATION, WARRANTY OR GUARANTEE (i) THAT ANY RESULTS DESCRIBED IN THIS DOCUMENT WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN OR APPLICATION INCORPORATING SELLER'S MATERIALS, PRODUCTS, SERVICES OR RECOMMENDATIONS. UNLESS OTHERWISE PROVIDED IN SELLER'S STANDARD CONDITIONS OF SALE, SELLER SHALL NOT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS, SERVICES OR RECOMMENDATIONS DESCRIBED IN THIS DOCUMENT. Each user is responsible for making its own determination as to the suitability of Seller's materials, products, services or recommendations for the user's particular use through appropriate end-use and other testing and analysis. Nothing in any document or oral statement shall be deemed to alter or waive any provision of Seller's Standard Conditions of Sale or this Disclaimer, unless it is specifically agreed to in a writing signed by Seller. Statements by Seller concerning a possible use of any material, product, service or design do not, are not intended to, and should not be construed to grant any license under any patent or other intellectual property right of Seller or as a recommendation for the use of any material, product, service or design in a manner that infringes any patent or other intellectual property right.

SABIC and brands marked with ™ are trademarks of SABIC or its subsidiaries or affiliates, unless otherwise noted. © 2023 Saudi Basic Industries Corporation (SABIC). All Rights Reserved. Any brands, products or services of other companies referenced in this document are the trademarks, service marks and/or trade names of their respective holders.

www.SABIC.com SABIC-PLA-26127-EN